





Hydro Solo-E CR(N)32, CR(N)45, CR(N)64, CR(N)90- 3 phase with Variable Frequency Drive (VFD)

* Drawings not to scale

| MODELS | HP | Supply Voltage | | | | System connection | Dimensions (mm) | | | | | | | Weight (lbs) | Shipping Volume (ft ³) |
|--------------|----|----------------|--------------|----------|----------|-------------------|-----------------|-------|-------|-------|--------|--------|-------|--------------|------------------------------------|
| | | 1 x 230V | 3 x 208-230V | 3 x 460V | 3 x 575V | | B1 | B2 | B3 | B4 | H1 | H2 | H3 | | |
| CR 90 | | | | | | | | | | | | | | | |
| CR 90-1 | 15 | | • | • | • | 4" 150 LB ANSI | 883.0 | 287.6 | 570.0 | 636.0 | 1140.0 | 1224.4 | 199.9 | 973.5 | 57.0 |
| CR 90-2-2 | 25 | | • | • | • | 4" 150 LB ANSI | 883.0 | 287.6 | 570.0 | 636.0 | 1140.0 | 1382.5 | 199.9 | 1121.5 | 57.0 |
| CR 90-2-1 | 30 | | • | • | • | 4" 150 LB ANSI | 883.0 | 287.6 | 570.0 | 636.0 | 1140.0 | 1420.5 | 199.9 | 1136.5 | 57.0 |